

898.00 EUR
incl. 19% VAT, plus [shipping](#)



- INTEL® Broadwell I5 5200U SoC Processor
- 2 * SO-DIMM (Dual Channel DDR3L 1333/1600MHz SDRAM)
- Support CPU Smart FAN
- Giga LAN Port * 2
- Support 10/100M/1000M Base-TX RJ45 Ports * 4
- Support Watch dog Technology
- Support AC 90~240V input
- Applications ■ Industrial Control System ■
Networking Server System ■ Security Industry

| | |
|---------------------|--|
| • Product Dimension | • 264 (W) * 199.4 (D) * 38 (H) mm |
| • Product Model | • JBC512F3EG(W)-5200-B |
| • MB Model & Size | • NF3EP-5200 / 3.5" SBC |
| • BIOS | • AMI 32MB SMT Flash ROM |
| • CPU | • INTEL® Broadwell I5 5200U |
| • Memory | • 2 * SO-DIMM (Dual Channel DDR3L 1333/1600MHz SDRAM) |
| • Storage Space | • 2.5" SATA Device * 1 |
| • Colors | • Black |
| • Front I/O Port | • 4 PIN AC Input * 1 • AC ON-OFF * 1 • Power LED * 1 • Power SW * 1 • USB 2.0 * 2 |
| • Rear I/O Port | • USB3.0 * 4 , USB2.0 * 2 • HDMI * 2 • Giga LAN Port * 2 • Audio * 1 • WiFi Port * 2 (JBC512F3EGW-5200-B only) |
| • POE Port | • 10/100M/1000M Base-TX RJ45 Ports * 4 • Conforms to IEEE802.3af, IEEE802.3at • IEEE 802.3x full-duplex flow control, per port up to 23W • Provides 4 PoE injector, per port DC52.5V-0.48A-25W • For Switch : Marvell 88E6176 • For PoE : MAX5980 |
| • Power Source | • 150W AC to DC OP Power inside • AC 90~240V input |
| • Accessory | • AC Cable * 1 • 4 Pin Terminal block con * 1 • User Manual * 1 • CD * 1 • Screw Package * 1 |

| | |
|-----------------|--|
| • Packing | <ul style="list-style-type: none">• Net Weight■3.6KG• Gross Weight■4.5KG• Color Box Dimension■406 (W) x 148 (D) x 359 (H) mm |
| • Temperature | <ul style="list-style-type: none">• Operating within 0~50 centigrade• Storage within -10-70 centigrade |
| • Certification | <ul style="list-style-type: none">• EMC : CE , FCC• Safety : RoHS , ErP |
| • Applications | <ul style="list-style-type: none">• Industrial Control System• Networking Server System• Security Industry |