

369.00 EUR
incl. 19% VAT, plus [shipping](#)



- Intel® Apollo Lake N3350/N4200 SoC Processor
- Support 1 * DDR3L 1866MHz SO-DIMM up to 8GB
- 2 * USB3.0 ,1 * GbE LAN ,1 * HDMI , 1 * Micro SIM
- Support M.2 (M-key, SATA interface, 2242) storage
- M/B Form Factor : PICO SBC (100x72mm)
- DC-12V_40W Adapter

| | |
|-----------------|---|
| MB Model | – JNP691-3350 / PICO SBC – JNP691-4200 / PICO SBC |
| Part No | – HBJC400P691-335B / HBJC400P691-420B (non-WIFI) – HBJC400P691W-335B / HBJC400P691W-420B (WIFI) |
| BIOS | – AMI Flash ROM |
| CPU/Chipset | – Intel® Apollo Lake N3350/N4200 SoC Processor |
| Memory | – 1 * DDR3L-1866 SO-DIMM slots up to 8GB total |
| Storage | – 1 * M.2 – 2242 (M-KEY) |
| Expansion Slot | – 1 * Full-size mini-PCIE slot (for 802.11 b/g/n + BT 4.0 installed in WIFI model) |
| Network | – 1 * Realtek RTL8111H GbE |
| Rear I/O Port | – 2 * USB 3.0 ports – 1 * HDMI (Max. resolution: 3840x2160@30Hz) – 1 * RJ45 – 1 * SIM Card Holder – 1 * Kensington lock – 3 * Antenna holes – 1 * DC Jack |
| Front Panel I/O | – 1 * Power button – 1 * Power LED |
| Power Source | – AC-DC FSP Adapter / DC12V-3.3A-40W – AC 90~240V input |
| Compliance | – CE, FCC, RoHS, ErP Ready |
| Temperature | – Operating Temperature : 0°C~50°C – Storage Temperature : -20°C~70°C |
| Dimensions | – 129 (W) x 78.4 (D) x 34 (H) mm |

| | |
|------------|---|
| Packing | <ul style="list-style-type: none">- Net Weight: 0.8KG- Gross Weight■1.5KG- Color Box Dimension■156 (W) * 167 (D) * 123.6 (H) mm |
| OS Support | <ul style="list-style-type: none">- Windows 10 , Linux |
| Warranty | <ul style="list-style-type: none">- 2 Year limited warranty |