



479.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel Kabylake-U !
- 2x Gigabit LAN !
- With fan !
- 1 Liter enclosure !

Support: [Specifications](#)

S320-11KS is a box pc, powered by the 7th gen Kabylake-U performanceenhanced processor. The whole system is 1 liter size but still with versatile I/O aiming to adapt it in different environments and wide applications.

Long term availability until at least 2023 !

For a full PC you need in addition :

- mSATA SSD
- RAM

SYSTEM

CPU

7th Generation Kabylake Intel® Core™ i ULV Processor
(Default: i3-7100U; Compatible with i7-7600U, i5-7300U, Celeron 3965U)

Option: 6th Generation Skylake Intel® Core™ i ULV Processor
(Compatible with i7-6600U, i5-6300U, i3-6100U, Celeron 3955U)

CHIPSET

Intel® SoC integrated

SYSTEM MEMORY

DDR4 2133/2400, 260-pin SO-DIMM x 2, Max. 32 GB (Non-ECC)

GRAPHICS

Intel® HD Graphics

DISPLAY INTERFACE

DP, HDMI

STORAGE SLOT

mSATA x 1

ETHERNET

Intel® I219LM Giga LAN + I211AT Giga LAN

AUDIO

Realtek ALC283

I/O CHIPSET

Nuvoton NCT6104D

TPM

Nuvoton NPCT650ABCYX TPM2.0

EXPANSION SLOT

Storage: PCI Express Full-Length Mini Card slot (USB / PCIe / SATA)

Wireless: M.2 2230 E key (PCIe / USB)

FRONT I/O

HDD LED

Power Button w/ Power Indicator

| | |
|------------------------|--|
| REAR I/O | DC-in x 1 Audio Combo Jack (Mic-in and Line-out) x 1 DP x 1 HDMI x 1 RJ-45 x 2 USB 3.0 x 4 SMA Antenna (Option for WiFi function) Temperature Monitor, Voltage Monitor 1~255 Steps by Software Program Power LED, HDD LED |
| H/W MONITOR | |
| WATCHDOG TIMER | |
| INDICATOR | |
| POWER REQUIREMENT | |
| POWER INPUT | 8~24V Wide Range DC-in Jack Connectivity (Default) 8~24V Wide Range DC Input w/ Terminal Block Connectivity (Optional) AC to DC, DC19V/ 3.4A, 65W adaptor |
| POWER ADAPTER | |
| MECHANICAL | |
| MOUNTING | Wallmount Kit (Default in Accessories) |
| DIMENSIONS (W X D X H) | 7.3" x 4.9" x 1.8" (185mm x 125mm x 45mm) |
| MATERIAL | Top cover: Aluminum Alloy , Bezel and chassis: Steel |
| ENVIRONMENTAL | |
| OPERATING TEMPERATURE | 0~50°C |
| STORAGE TEMPERATURE | -20~80°C |
| OPERATING HUMIDITY | 10%~90% (Non-condensing) |
| VIBRATION RESISTANCE | 5Hz~500Hz/ 2Grms/ 3Axis (Non-operating) |
| SHOCK RESISTANCE | 120G, 2ms Duration (Non-operating) |
| CERTIFICATION | CE & FCC |
| OS | |
| OS SUPPORT | KBL-U: Windows® 10, Linux support by request SKL-U: Windows® 10, Windows® 8.1, Windows® 7, Linux support by request |