

1598.00 EUR
 incl. 19% VAT, plus [shipping](#)

- Intel Tiger Lake !
- i5-1135G7 !
- 21,5" Panel Computer !



- 1. 21.5" 250 nits TFT LCD with LED backlight
- 10-points Multi Capacitive Touch
- Support Open frameless design
- Aluminum Die-Cast Panel PC series, Easy HDD and DARM installation, cableless design
- 12-36V DC-in, with Electrical Over Stress (EOS) and OVP design
- Front bezel meets IP65-rated protection
- VESA Support 100x100mm

Display	<ul style="list-style-type: none"> - IP65, NEMA 4 rugged protection, metal front bezel - 21.5" With LED Backlight - 250 nits - 16.7M display color - 1920 x 1080 @60Hz resolution - 170°/160° viewing angle (H/V) - 0.24825 x 0.24825mm pixel pitch - 16:9 aspect ratio - 1000:1 contrast ratio - 8ms response time
---------	---

Touch Screen	<ul style="list-style-type: none"> - Projected capacitive type - 386.81 x 237.12mm ±0.3mm active range - Transparency ■ 85% - Surface Hardness ■ 6H (JIS-5400)
Case	<ul style="list-style-type: none"> - Aluminum panel - Iron case - White color - Spray paint coating requirement
Main System	<ul style="list-style-type: none"> - Intel® Tiger Lake i5-1135G7 2.4GHz/QC processor - 2* DDR4 SO-DIMM (Max 64GB) - 256MB SPI Flash ROM - Watchdog Timer 256 levels, 0~255 sec. - OS Support Windows 10 / Linux
Expansion	<ul style="list-style-type: none"> - 1* M.2 E key (2230) for WIFI - 1* M.2 B key (3042/3052/6570) for 4G/5G Module (4pcs Built in Antenna)
Storage	<ul style="list-style-type: none"> - 1* 2.5" SATA HDD - 1* M.2 M key (2242/2280, PCI-Ex4)
I/O Connector	<ul style="list-style-type: none"> - 2* USB3.2 (Gen. 2) - 4* USB2.0 - 2* RS232/422/485 - 2* RS232 (option 16bit GPIO) - 1* HDMI - 1* AT/ATX Mode Button - 2* RJ45 (1* Intel® I225-V 2.5GbE, 1* Intel® I219LM GbE) - 1* 12~36V DC-in Locking Jack - 1* Power button - 1* 2pin Front Power button
Power Input	<ul style="list-style-type: none"> - 12~36V DC-in - AC version: 100~240V AC-DC 90W power adapter or - DC version: 12VDC with over current protection fuse
Power Consumption	<ul style="list-style-type: none"> - 45W
Dimensions	<ul style="list-style-type: none"> - 535.80 * 327.31 * 68.50 mm
Compliance	<ul style="list-style-type: none"> - CE, FCC, IP65 (Front, option)
Safety	<ul style="list-style-type: none"> - Shock: 1ms duration - Vibration: 5~500Hz/1 Grms
Temperature	<ul style="list-style-type: none"> - Operating: : -10°C ~ 60°C - Storage: -20°C ~ 70°C