



169.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel 945GM
- VGA + DVI !
- Mini-PCI slots
- 2x COM Port !

- Intel 945GM+ICH7M chipset Technology
- Support Intel Core 2 Duo Mobile processor
- Support Front Side Bus 667MHz
- Dual Channel DDR2 667 Memory up to 2GB
- Support 2 Serial ATA2 Devices
- Dual Gigabit Ethernet LAN Support
- Dual COM Port
- DualView (VGA + DVI)
- 6 Channel HD Audio CODEC
- 1x Mini-PCI, 1x Mini-PCI Express

|                      |                                                                                                                       |
|----------------------|-----------------------------------------------------------------------------------------------------------------------|
| Form Factor          | Mini-ITX 170 mm x 170 mm                                                                                              |
| CPU                  | Support Core 2 Duo, Core Duo, Core Solo Mobile Processor<br>Front Side Bus 667 / 533 Mhz<br>Package Type: Socket 479m |
| Memory               | 2 * Dual Channel 240-pin DIMM Sockets for unbuffered DDR2 667 up to 2GB                                               |
| Chipset              | Intel 945GM Express Chipset and ICH7M Chipset                                                                         |
| Power Management     | ACPI S3 Compliant , supports Power Saving Mode                                                                        |
| PCI Enhanced IDE     | 2 * Ultra DMA 100 / 66 IDE Devices Support                                                                            |
| Serial ATA Interface | 2 * Serial ATA2 HDDs                                                                                                  |
| VGA Interface        | Intel Graphics Media Accelerator 950                                                                                  |
| Video Memory         | Share Memory up to 224MB                                                                                              |
| LVDS Interface       | Onboard 18-bit dual channel LVDS connector                                                                            |
| Audio Interface      | REALTEK ALC 888 6-Channel HD Audio CODEC                                                                              |
| LAN Interface        | Dual REALTEK RTL8111B 10 / 100 / 1000 PCI-E LAN                                                                       |
| Extended Interface   | 1 * 32-bit PCI slot<br>1 * Mini PCI<br>1 * Mini PCI Express x1 Slot                                                   |

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Internal I/O Port | <p>2 * High Speed USB Connectors @ 480 M-bit / s for 4 USB 2.0 Ports</p> <p>1 * CPU Smart Fan Connector, 2 * DC Fan Connectors</p> <p>1 * CD / AUX Audio in &amp; SPEAK Out</p> <p>1 * HDTV Output Connector</p> <p>1 * LVDS Connector, 1 * LVDS Inverter Connector</p> <p>1 * IEEE1394 Connector</p> <p>1 * PS/2 connector for Keyboard and Mouse</p> <p>1 * IrDA (CIR) (Need to purchase optional IR Receiver and Remote Control)</p> |
| External I/O Port | <p>4 * High Speed USB Connectors @ 480 M-bit / s</p> <p>1 * DVI-D Port</p> <p>1 * D-sub 15-pin VGA Connector</p> <p>1 * HDMI Port</p> <p>2 * RJ45 Connector and 2 * Serial COM Ports</p> <p>1 * Mic-In connector, 1 * Audio input connector, 1 Audio Output connector.</p>                                                                                                                                                              |
| BIOS              | Award 8 MB Flash ROM                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Power Requirement | Standard 24-pin ATX Compliance Power Supply                                                                                                                                                                                                                                                                                                                                                                                             |
| Dimension         | 170mm x 170mm                                                                                                                                                                                                                                                                                                                                                                                                                           |