

the best regional partners



MINI-PC Pluto E220


A lot of PC in a little package

Looking for a thin client that is as versatile as it is compact? We have the solution. Our Pluto E220 is built around the latest generation of Intel's Baytrail. Baytrail has been improved 3D graphics performance with up to 5x more power and 2x greater CPU performance over previous generation. The whole new SOC structure packs more powerful capability for your tasks or applications.

The E220's 2.2 liter fanless chassis design gives it the flexibility to adapt to every workspace and environment, whether implemented as a nettop or thin client. VESA mount support allows for space-saving rear-mounting on flat-screen displays. Flexibility also means a rich array of I/O ports to add a variety of peripherals. Storage expandability is supported for high-density hard drives. Wireless card interface allows effortless connection to Wi-Fi networks. Extend your visual experience with support for dual displays.



Fanless design



Versatile interfaces



VESA mounting



Wireless (Optional)



Dual Display

**HDD
mSATA**

HDD/ mSATA
support

MINI-PC Pluto E220

A lot of PC in a little package



VESA mount support



Vertical and horizontal orientation



Fanless design



mSATA/HDD/SDD support



Wireless support (Option)



Dual LAN (Option)



Dual Display



Versatile interfaces

Item	Spec	Optional
Processor	Intel Bay Trail Desktop J1900	J1800
Chipset	SoC	
OS support	Linux, Win 7, Win 8, Android	
PCB	Mini-ITX proprietary, 4 layer, 182mm x 185mm	
Memory	DDR3, 1333MHZ, (2 x So-DIMM slot, up to 8GB)	
LAN	Realtek RTL8111E GLAN x2	Single LAN
Audio	Realtek ALC-662	
Storage	SATA DOM or 2.5" SATA HDD/SSD or mSATA	
Mini Card	1 Full-length for mSATA One-sided screw 1 Half-length for wireless module	
WLAN support	For 802.11 b, g, n	Wireless Card Antenna
Display interface	1 x DVI-I, 1 x HD Out	
SPI Flash	16Mb	
Front I/O	1 x USB3.0, 1 x USB2.0, MIC-in, Headphone-out, power button	
Rear I/O	2 x PS/2, 4 x USB2.0, 1 x Ethernet RJ45, 1 x DVI-I, 1 x HD out, 2 x Serial Port, 1 x DC jack, 1 x Kensington lock	Parallel Port can be removed
Internal speaker	1 x Buzzer As default	Speaker is the option
Power supply	65W, 19V, Power Adapter	
Chassis Dimension	220 x 195 x 50mm (Fanless)	
Environmentals	Fanless System Temp: 10 Degree C~ 35 Degree C Humidity: 20%~85% Non-Condensing MB Temp: 0~60 Degree C	
VESA Mount	Yes (100mm x 100mm)	
VESA Bracket Stand	For vertical use	Support 75x75 and 100x100 VESA standard